













NATIONAL WEATHER SERVICE

# Rapid Refresh Forecast System A case study for using cloud resources to reduce R2O transition times

**October 22, 2020** 

EMC: Arun Chawla, Jacob Carley, James Abeles, Raj Panda

GSL: Curtis Alexander, Christina Holt, Christopher Harrop, Daniel Abdi

**NSSL**: Louis Wicker







# **Outline**

NPS Production Suite and UFS

RRFS

Using the Cloud for development







#### **Shared Community Infrastructure Support for UFS Development**

Infrastructure for data assimilation:
Joint Effort for Data assimilation Integration
(JEDI)

1. Coupling components

New ESMF/NUOPC mediator (CMEPS/NEMS)

2. Interoperable atmospheric physics

CCPP & CPF frameworks

**3. Community-friendly workflow**CIME - CROW unification, CIME Case Control System

**4. Hierarchical model development capabilities**Extensions of CIME data models, unit, & system testing

**5. Forecast Verification: Comparison to Observations**Extension of MET+

6. Software Repository Management

NCAR manage\_externals tool

**7. User / Developer Support** DTC and CESM Capabilities

**NOAA-NCAR MoA Work Areas** 

#### Infrastructure for coupling models together:

- NOAA Environmental Modeling System (NEMS) coupler
- based on the Earth System Modeling Framework (ESMF)
- using National Unified Operational Prediction Capability (NUOPC) conventions

#### Infrastructure for interoperable physics:

- Common Community Physics Package (CCPP) framework
- Infrastructure for Code Management:
- Git based repositories with Gitflow







### ž

# NPS Transitioning to UFS Applications





















#### **Toward a simpler, UFS-based Production Suite (notional)**










## **UFS: Simplification of Regional Model Production Suite**







# The Rapid Refresh Forecast System

- Rapid Refresh Forecast System (RRFS)
  - Based on the UFS-Limited Area Model (LAM)
    - Underpinned by the Finite-Volume Cubed-Sphere dynamical core (FV3)
  - Rapidly updated (hourly)
  - Convection-allowing (~3 km)
  - Ensemble data assimilation (est. 30 or 40 members)
  - Ensemble forecasts (est. 10 members)
    - 18h+ hourly
    - 36-60h every 6 to 12 hours
- When? ~FY23
- Exact configuration for data assimilation still under development
- Facilitate replacement of several current regional systems
  - e.g., NAM+nests, RAP +HRRR, HiRes Windows, HREF
- How do we get there? And with what resources?


















#### **LAM vs Nest**

- FV3 was originally a global model with a nesting capability
  - No limited area component
- Practical reasons drive need for LAM
  - More efficient
  - Focused development
  - Rapidly updating data assimilation, etc.
  - Little impact on forecast quality for short-range forecasts








#### **LAM vs Nest Clock Times**


- औ
- **\***

- 员
- 1

- Using NOAA Hera R&D HPC System
- LAM needs less than half tasks required to get output in same amount time as NEST
- For a given set of tasks, the LAM completes the forecast in about half the amount of time as NEST










郊

# RRFS Development Resource Needs

湾

\*

**NATIONA** 



resources that are not currently available to developers

**Nation** // 11



\*>

#### Can We Do this on the Cloud?

- Hurricane Disaster Supplemental Supported Project
- Port, deploy, and test RRFS prototype(s) in the cloud
- Flexible
  - If this works it opens many possible doors for future R&D resource needs, especially for early development that may not need real time testing
- UFS has been run in the cloud before
  - Efforts to put RRFS on cloud will enhance system portability for the UFS infrastructure
- Is cloud HPC slow?
  - #136 on June 2019 top500 list is a cloud instance!

	Rmax	Rpeak
Cores	(TFlop/s)	(TFlop/s

3,981.3

136 Descartes Labs United States

Amazon EC2 Instance Cluster C5, Xeon Platinum

Amazon EC2 C5 Instance cluster us-east-1a -

8124M 18C 3GHz, 25G Ethernet

Amazon Web Services





41,472 1,926.4



#### Moving to the Cloud - overview



- Preprocessing, Data Assimilation, Forecast, Post Processing, Visualization, etc.
- Performance characteristics & requirements
  - Some components (e.g. forecast) will need 10s of nodes with fast interconnect
  - Some (e.g. Post Processing) will need only a few nodes with moderate speed interconnect
- Data movement & storage
  - Data movement between NOAA HPC systems and the Cloud
  - Publicly available data access via internet into the Cloud
  - Majority of data storage in the Cloud and some in NOAA systems
- Workflow
  - All computing components and data movement tied together through workflow





#### Architecture




























#### Cloud deployment

- Resource mapping
  - Map each computing component to specific Cloud services/resources must meet performance or run time requirements
  - Type of instance, choice of file system, storage, etc.
- Cost estimation
  - Cloud offers a wide variety of computing resources with varying cost structures
  - Estimate cost of computing with the chosen resources
- Workflow
  - Ensure enabled workflow meets performance and cost estimates
- Ongoing
  - Cloud Service Providers (e.g. AWS) are constantly revising cost structures, adding new hardware and features several times a year
  - Multi-year project such as RRFS would need periodic assessment & revision of deployment to reduce cost

















#### Resource mapping & cost estimation - UFS example

- Applications built on NOAA systems can run on AWS instances
  - Preliminary work indicated binaries from WCOSS & RDHPCS (Orion, Hera) systems can run in AWS
  - AWS "c5n" instances and NOAA systems (WCOSS Phase3.5, Orion, Hera) have similar (Intel Xeon Skylake) processors
  - UFS can be run on AWS "c5n" instances with similar performance as on NOAA systems
- Use NOAA systems for performance optimization
  - Much optimization (configuration-related) work can be done on WCOSS & RDHPCS systems – saves spending money on Cloud systems
  - Verification work needs to be done in the Cloud
- Estimate AWS cost for optimized application configuration
  - Cores per node is different: 40 cores/node on WCOSS & RDHPCS while 36 cores/node on AWS "c5n" instances


















#### UFS - CONUS (details)

- Grid dimensions (1741 x 1037)
- Time step = 36s
- Forecast duration = 60 hours
- History file output = every hour
- CCPP Physics scheme: FV3\_GFS\_v15\_thomson\_mynn


















#### UFS - CONUS (60hr forecast on Hera)


















#### UFS - CONUS 60hr forecast on Hera (node-hours)


















#### Cost estimation for AWS - unknowns


- Flexibility in run time (e.g. can be > 3hrs) -> use of different instance types
  - Best interconnect (EFA) only comes with more expensive instance types
  - If 10g Ethernet performance is acceptable may lead to more costeffective computing
- File system performance
  - Multiple options (parallel Lustre & EFS) available will require benchmarking
- Processor frequency differences





Collaborative engagement at NOAA testbeds is a critical part of the development process for RRFS. Some of our cloud resources will be used to execute RRFS prototype components for testbed evaluation.









# Closing



- RRFSv1 planned for implementation in 2023 timeframe
  - Next generation, rapidly-updated convection-allowing NWP system
- Leveraging the cloud for development
  - Expand beyond conventional compute resources
- Project is in early phases
- Prototype systems to be demonstrated at upcoming NOAA Testbeds (HWT, FFaIR, WWE)



